

Shell Helix HX5 15W-50

Premium multi-grade motor oil - Helps to remove sludge from dirty engines



Shell Helix HX5 is designed to help provide consistent engine performance. It works hard to help protect against engine sludge and reduce wear. It is suitable for a wide variety of vehicles for everyday driving conditions.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

Active cleansing technology
Actively locks away harmful performance-robbing deposits.

• Effective wear protection 1

Helps to protect against wear and neutalise corrosive combustion acids.

High viscosity

Helps to reduce leaks in older, high-mileage engines.

· Resistance to oil degradation

Helps to maintain protection throughout the oil-drain interval.

· Multi-fuel capability

Can be used for gasoline, diesel and gas engines, and is also suitable for biodiesel and gasoline/ethanol blends.

Main Applications

 Shell Helix HX5's premium multigrade formulation helps to provide protection in everyday daily driving conditions. Shell Helix HX5 can be used for gasoline, diesel and gas engines, and it is also suitable for biodiesel and gasoline/ethanol blends.

Specifications, Approvals & Recommendations

- API SL/CF
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Shell Helix HX5
Viscosity Grade				15W-50
Kinematic Viscosity	@100°C	cSt	ASTM D445	18.94
Kinematic Viscosity	@40°C	cSt	ASTM D445	148.10
Viscosity Index			ASTM D2270	148
MRV	@-40°C	Ср	ASTM D4684	24700
Density	@15°C	kg/m³	ASTM D4052	872.4
Flash Point		°C	ASTM D92	252
Pour Point		°C	ASTM D97	-39

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

¹ Based on sequence IVA engine test carried out at an independent laboratory

Health, Safety & Environment

· Health and Safety

Shell Helix HX5 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from http://www.epc.shell.com/

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.